

• **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listing, of claims in the application.

Listing of Claims:

1. (Currently Amended) A light guiding plate comprising:
a light incident portion into which light is incident from a light source;
a light reflecting pattern to reflect the light provided from the light incident portion; and
a light transmitting surface to transmit the light reflected by the light reflecting pattern to a display panel,

wherein the light reflecting pattern includes a plurality of light reflecting sections each of which has:

a first light reflecting plane that is inclined with respect to the light transmitting surface to face toward the light source; and

a second light reflecting plane that is inclined with respect to the light transmitting surface and connected with an edge of the first light reflecting plane so that the light reflection sections each form a prism shape, the light reflecting sections respectively having the second light reflecting planes that are configured to have different areal sizes to control reflectivity of the respective light reflecting sections,

wherein the areal sizes of the second light reflecting planes are gradually increased by a selected amount such that the areal size of a second light reflecting plane is larger as the second light reflecting plane is remoter from the light incident portion, and

wherein the first light reflecting planes of the light reflecting sections respectively have first angles with respect to the light transmitting surface, and the second light reflecting planes of the light reflecting sections respectively have second angles with respect to the light transmitting surface, the first angles having a substantially identical value and the second angles being gradually decreased by a selected amount such that the second angle of a second light reflecting plane is smaller as the second light reflecting plane is remoter from the light incident portion.

2. – 3. (Cancelled)

4. (Currently Amended) The light guiding plate of claim 13, wherein the light reflecting sections each have a substantially identical height.

5. – 7. (Cancelled)

8. (Currently Amended) AThe light guiding plate comprising of claim 1,;
a light incident portion into which light is incident from a light source;
a light reflecting surface on which a light reflecting pattern is formed to reflect the light
provided from the light incident portion; and
a light transmitting surface to transmit the light reflected by the light reflecting pattern to a
display panel,
wherein the light reflecting pattern includes a plurality of light reflecting sections
protruding from the light reflecting surface, each of the light reflecting sections comprising:
a first light reflecting plane that is inclined with respect to the light transmitting
surface to face toward the light source; and
a second light reflecting plane that is inclined with respect to the light transmitting
surface and connected with an edge of the first light reflecting plane so that the light
reflection sections each form a prism shape, the light reflecting sections respectively having
the second light reflecting planes that are configured to have different areal sizes to control
reflectivity of the respective light reflecting sections,
wherein areal sizes of the light reflecting sections are gradually increased by a selected
amount such that the areal sizes of the first light reflecting plane and the areal size of the second
light reflecting planes of a light reflecting section are larger as the light reflecting section is remoter
from the light incident portion.

9. (Original) The light guiding plate of claim 8, wherein the first light reflecting planes of the light reflecting sections respectively have first angles with respect to the light transmitting surface, the second light reflecting planes of the light reflecting sections respectively have second angles with respect to the light transmitting surface, and the light reflecting sections each have different heights, wherein the first angles have a substantially identical value, the second angles

have a substantially identical value, and the heights are gradually increased by a selected amount such that the height of a light reflecting section is larger as the light reflecting section is remoter from the light incident portion.

10. (Currently Amended) A liquid crystal display device comprising:
- a lamp assembly to generate light in a linear direction;
 - a display panel assembly to display images using image data externally provided and light provided in a planar direction; and
 - a light guiding plate comprising:
 - a light incident portion into which the light is incident from the lamp assembly;
 - a light reflecting pattern to reflect the light provided from the light incident portion; and
 - a light transmitting surface to transmit the light reflected by the light reflecting pattern to the display panel assembly,
- wherein the light reflecting pattern includes a plurality of light reflecting sections each of which has:
- a first light reflecting plane that is inclined with respect to the light transmitting surface to face toward the light source; and
 - a second light reflecting plane that is inclined with respect to the light transmitting surface and connected with an edge of the first light reflecting plane so that the light reflection sections each form a prism shape, the light reflecting sections respectively having the second light reflecting planes that are configured to have different areal sizes to control reflectivity of the respective light reflecting sections,
- wherein the areal sizes of the second light reflecting planes are gradually increased by a selected amount such that the areal size of a second light reflecting plane is larger as the second light reflecting plane is remoter from the light incident portion, and
- wherein the first light reflecting planes of the light reflecting sections respectively have first angles with respect to the light transmitting surface, and the second light reflecting planes of the light reflecting sections respectively have second angles with respect to the light transmitting surface, the first angles having a substantially identical value and the second angles being gradually

decreased by a selected amount such that the second angle of a second light reflecting plane is smaller as the second light reflecting plane is remoter from the light incident portion.

11. – 12. (Cancelled)

13. (Currently Amended) The liquid crystal display device~~light guiding plate of claim 10~~¹¹, wherein the light reflecting sections each have a substantially identical height~~the first light reflecting planes of the light reflecting sections respectively have first angles with respect to the light transmitting surface, and the second light reflecting planes of the light reflecting sections respectively have second angles with respect to the light transmitting surface, the second angles having a substantially identical value and the first angles being gradually increased by a selected amount such that the first angle of a first light reflecting plane is larger as the first light reflecting plane is remoter from the light incident portion.~~

14. (Currently Amended) A liquid crystal display device comprising:~~The light guiding plate of claim 10,~~

a lamp assembly to generate light in a linear direction;

a display panel assembly to display images using image data externally provided and light provided in a planar direction; and

a light guiding plate comprising:

a light incident portion into which the light is incident from the lamp assembly;

a light reflecting surface on which a light reflecting pattern is formed to reflect the light provided from the light incident portion; and

a light transmitting surface to transmit the light reflected by the light reflecting pattern to the display panel assembly,

wherein the light reflecting pattern includes a plurality of light reflecting sections protruding from the light reflecting surface, each of the light reflecting sections comprising:

a first light reflecting plane that is inclined with respect to the light transmitting surface to face toward the light source; and

a second light reflecting plane that is inclined with respect to the light

transmitting surface and connected with an edge of the first light reflecting plane so that the light reflection sections each form a prism shape, the light reflecting sections respectively having the second light reflecting planes that are configured to have different areal sizes to control reflectivity of the respective light reflecting sections,
wherein areal sizes of the light reflecting sections are gradually increased by a selected amount such that the areal sizes of the first light reflecting plane and the areal size of the second light reflecting planes of a light reflecting section are larger as the light reflecting section is remoter from the light incident portion.

15. (Currently Amended) The liquid crystal display device~~light guiding plate~~ of claim 14, wherein the first light reflecting planes of the light reflecting sections respectively have first angles with respect to the light transmitting surface, the second light reflecting planes of the light reflecting sections respectively have second angles with respect to the light transmitting surface, and the light reflecting sections each have different heights, wherein the first angles have a substantially identical value, the second angles have a substantially identical value, and the heights are gradually increased by a selected amount such that the height of a light reflecting section is larger as the light reflecting section is remoter from the light incident portion.

16. (Withdrawn) A method for displaying images in a liquid crystal display device, comprising:
generating light in a linear direction;
transforming the light in a linear direction into light in a planar direction, the transforming step including:
providing light reflecting sections each having a different reflectivity; and
reflecting the light in a linear direction at the light reflecting sections to obtain the light in a planar direction, a light reflecting section having higher reflectivity as the light reflecting section is remoter from a light source generating the light in a linear direction; and
displaying images using the light in a planar direction and image data externally provided.

17. (Withdrawn) The method of claim 16, wherein the reflecting step includes varying the

reflectivity of the respective light reflecting sections by changing areal sizes of the light reflecting sections such that the area size of a light reflection section is larger as the light reflection section is remoter from the light source.

18. (Withdrawn) The method of claim 17, wherein the light reflecting sections each have a prism shape with first and second light reflecting planes and a bottom plane, the varying the reflectivity of the respective light reflecting sections including:

maintaining a first angle between the first light reflecting plane and the bottom plane substantially constant in all the light reflecting sections; and

decreasing a second angle between the second light reflecting plane and the bottom plane such that the second angle of a light reflecting section is smaller as the light reflecting section is remoter from the light source.

19. (Withdrawn) The method of claim 17, wherein the light reflecting sections each have a prism shape with first and second light reflecting planes and a bottom plane, the varying the reflectivity of the respective light reflecting sections including:

increasing a first angle between the first light reflecting plane and the bottom plane such that the first angle of a light reflecting section is larger as the light reflecting section is remoter from the light source; and

maintaining a second angle between the second light reflecting plane and the bottom plane substantially constant in all the light reflecting sections.

20. (Withdrawn) The method of claim 17, wherein the light reflecting sections each have a prism shape with first and second light reflecting planes and a bottom plane, the varying the reflectivity of the respective light reflecting sections including:

maintaining angles between the first and second light reflecting planes and the bottom plane substantially constant in all the light reflecting sections; and

increasing a height of the respective light reflecting sections such that the height of a light reflecting section is larger as the light reflecting section is remoter from the light source.